PRODUCT PECIFICATION



Direct Service • Dynamic Solutions

EMG-LEDT8-*-*



LED T8 Emergency tubes

661

| Diffuser | Frosted |
|-----------|---------|
| | |
| Material: | PC |



| Supply Voltage | 230Vac |
|------------------------|-------------------------|
| Wattage | 9W / 18W / 22W |
| Colour Temp | CW (4200k) / DL (6000k) |
| Dimmable | No |
| Lumens | 88lm/w |
| Power Factor | 0.95 |
| Estimated Life Span | 50000hrs |
| Warranty | 2 Years |
| Colour Rendering Index | 75 |
| Battery Backup | 1hr @ 300lm |
| Battery | Integrated |
| Beam Angle | 270° |

ADDITIONAL INFO

| Packing Includes | LED tube + Warning Labels |
|------------------|---------------------------|
| Diameter | 26mm |
| Length | 600 / 1200 / 1500mm |

GENERAL INFORMATION


NB!! Emergency only works when switch is on and mains fail NB!! Tubes need to be wired independantly **Requires Surge Protection** Low Maintenance

INSTALLATION STEPS / OTHER INFO

- Product is ideal for indoor use or use in IP65 lighting fixtures
- Easy to install
- Installation to be done by a qualified electrician ٠



MAINS FAIL SWITCH ON / EMERGENCY ON \otimes FUSE LINK



COLOUR TEMPRETATURE

7500K 10,000 4100K 5000K **4200K** ▲6000K Daylight

Cool White

3500K

3000K